



SRX-XPOE1

	Item	Description
Power	Power Supply	PoE Power Supply
	Consumption	< 3W
Ethernet Port	Ethernet Port	PoE IN Port:10/100Mbps, PoE Input Port
		PoE OUT Port:10/100Mbps, PoE Output Port
	Transmission Distance	150m(About the relationship between distance and power, Please refer to table 1)
	Transmission Medium	Cat5e/6
	PoE Protocol	Support IEEE802.3af, IEEE802.3at Protocol
	PoE Mode	Compatible with End-span and Mid-span
Network Switch	Network Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX
	Network Delay	<20us
LED Status Indicator	LED	PoE IN Port and PoE OUT Port: RJ45 yellow light indicates PoE status; green light indicates data exchange
Protection	ESD	1a Contact Discharge Leve 3
		1b Air Discharge Level 3
	Communication port Lightning protection	Per: IEC61000-4-2
Environmental	Working temperature	-40°C~75°C
	Storage temperature	-40°C-85°C
	Humidity (non-condensing)	0-95%
Mechanical	Dimension (L×W×H)	103mm×82mm×25mm
	Material	Aluminum
	Color	Black
	Weight	195g
Stability	MTBF	>30000h