



SRX-MS16PP+ 16 Port POE Switch

Item		16 Ports Managed PoE Switch
Power	Power Supply	Mains on load
	Voltage Range	AC 100~240V
	Power Consumption	320W (Full load)
Network Connector	Ethernet Port	1~16 Ports: 10/100Mbps Ethernet port, adaptive control UPLINK Ethernet port: 10/100/1000Mbps Ethernet port SFP: SFP optical fiber module, 1000Mbps
	Transmission Distance	1~16 ports: Recommended 120m Max.150m; Uplink 1000Mbps Ethernet port: Max.100m SFP: depend on the optical module performance
	PoE Protocol	IEEE802.3af,IEEE802.3at
	PoE Power Supply	End-span
	PoE Power Consumption	Each Port≤30W, Total ≤250W
Network Switch	Ethernet Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX\LX
	Switch Capacity	16G
Management	Management	Management L2
Protection	ESD	Level 3, Per: IEC61000-4-2
	Communication Port Lighting Protection	Level 3, Per: IEC61000-4-5
Environmental	Working temperature	0℃~55℃
	Storage temperature	-40℃-85℃
	Humidity (non-condensing)	0-95%
Mechanical	Dimension (L×W×H)	442mm×315mm×44mm
	Material	Sheet metal
	Color	Black
	Weight	3.54kg