



SRX-IGS4PP+ 4 Port Endüstriel Gigabit Switch

Item		4 Ports Gigabit Ethernet PoE Switch
Power	Power Supply	Power Adapter
	Voltage Range	DC48V~57V
	Power Consumption	<6W
Ethernet PortPatameter	Ethernet Port	Combo port, SFP optical port: 1000Mbps
		Other optical port: 10/100/1000Mbps
	Transmission Distance	Ethernet port:100m;
		SFP optical port: depend on the optical module transmission performance
	Transmission Medium	Cat5e/6 standard network cable
	PoE agreement	IEEE802.3af, IEEE802.3at agreement
	PoE power supply	End-span
	PoE power	Single port≤30W
Ethernet	Ethernet Standard	IEEE802.3,IEEE802.3u,IEEE802.3ab, IEEE802.3z
Exchange	Exchange way	Store and forward
	Package data cache	1M
	MAC address list	8K
Status indicator	Power indicator	1 indicate power (Red)
	Optical port LED indicator	2 Fiber Link Green lights indicate fiber working status
	Uplink Ethernet port LED indicator	RJ45 port indicates network working status
	Downlink Ethernet port LED indicator	1~4 ports with green lights indicate network status, yellow light indicates PoE
Protection	Communication port	Level 3, Per : IEC61000-4-5
	ESD	Level 3, Per : IEC61000-4-2
		Level 3, Per : IEC61000-4-2
Environmental	Working temperature	-40°C~75°C
	Storage temperature	-40°C-85°C