



SRX-MS24PMX 24 Port 10/100/1000

Moduler Switch Data Sheet

Power	Power Supply	Mains on load
	Voltage Range	AC100V-240V
	Consumption	2X60W
Ethernet Port	Ethernet Port	24 ports: 10/100/1000Mbps Ethernet ports or 100/1000Mbps SFP ports
		Uplink:10/100/1000Mbps adaptive Ethernet port
		Uplink:1000Mbps SFP Module port
	Transmission Distance	Ethernet ports:100m SFP ports: depend on SFP module
Network Switch	Network Standard	IEEE802.3,IEEE802.3u,IEEE802.3ab,IEEE802.3z,IEEE802.3X,IEEE 802.1Q, IEEE 802.1p,IEEE 802.3ad
	Switch Capacity	70G
	MAC Address	16K
Management	Management	Management L2
Protection	ESD	Level 3 Pe:IEC61000-4-2
	Lighting Protection	Level 3 Per: IEC61000-4-5
Environmental	Working Temperature	0°C~55°C
	Storage Temperature	-40°C~85°C
	Humidity (non-condensing)	0~95%
Mechanical	Dimension (L×W×H)	442mm×315mm×44mm
	Material	Sheet Metal
	Color	Black
	Weight	3.78 kg



		SRX-RJM8 8 Ports Full Gigabit RJ45 Ethernet Module	SRX-SFM8 8 Ports Full Gigabit SFP Fiber Module
Network Ports	Network Ports	8 x 10/100/1000Mbps Ethernet ports	8 x Gigabit SFP ports
	Distance	Ethernet ports:100m	SFP: Maksium 100km
Mechanical	Dimension	137mm×91mm×44.5mm	
	Material	Metal	
	Weight	146g	142g