



SRX-SP201EP Ethernet ve 24V Enerji Hattı Yüksek Akım Korumucu

Item		Description	
Network	Model	USP201EP	USP201EP-AC220
	Rated Working voltage	5V	
	Maximum Continuous working voltage	6V	
	Nominal Discharge Current (8/20us)	3KA	
	Maximum Discharge Current (8/20us)	10KA	
	Voltage Limit Between Lines (10/700us)	01.Şub	<36V
		03.Haz	<36V
	Insulation Resistance	≥0.4MΩ	
	Insertion Loss	≤0.9dB	
	Bandwidth	(0.3-100) M	
	Transmission Rate	100MHz	
	Reacting Time	≤1ns	
Power	Rated Working Voltage	24V	220V
	Maximum Continuous Working Voltage	36V	320V
	Nominal Discharge Current (8/20us)	5KA	10KA
	Maximum Discharge Current (8/20us)	10KA	20KA
	Limiting Voltage (8/20us)	≤40V	≤200V
	Reacting Time	≤25ns	≤25ns
Environmental	Working Temperature	0°C~55°C	
	Storage Temperature	-20°C~70°C	
	Humidity (non-condensing)	0~95%	
Mechanical	Net weight	157g	
	Dimension	108mm*66mm*28mm (include interface length)	
	Material	Aluminum	
Stability	MTBF	>30000h	