

	Item	Description
Video	Rated operation voltage	5V
	Max continuous operating voltage	6V
	Nominal discharge current in(8/20μs)	5KA
	Max discharge current(8/20μs)	10KA
	Voltage protection level(10/700μs)	<20V
	Reacting time	≤1ns
	Inserting loss	≤0.2dB
	Inserting resistance	≤1Ω
	Signal Bandwidth	10MHz
	Port	BNC
Power	Nominal working voltage	24V
	Max continuous operating voltage	36V
	Nominal discharge current(8/20μs)	5KA
	Max discharge current (8/20μs)	10KA
	Limiting voltage (8/20μs)	<200V
	RLA	≤10A
	Leakage Current	≤5μA
	Reacting Time	≤25ns
Control Signal	Rated operation discharge	5V
	Max continuous operating voltage	6V
	Nominal discharge current(8/20μs)	5KA
	Max discharge current(8/20μs)	10KA
	Impulse limiting voltage(10/700μs)	<20V
	Insulation resistance	≥0.4MΩ
	Insertion loss	≤0.5dB
	Standing-wave ratio	≤1.2
	Transmission Rate	<2Mbps
Environmental	Reacting time	≤1ns
	Working temperature	-20～50℃
	Storage temperature	-40～70℃
	Humidity (Non-Condensing)	0～95%
Mechanical	Dimension	112mm*64mm*38 mm
	Material	Aluminum
	N.W.	178g
Stability	MTBF	>30000hrs