



SRX-POET1 POE Medya Dönüştürücü

	Item	Description
Power	Power Supply	Power Adapter
	Voltage Range	DC 48V-57V
	Consumption	<35W (PoE power supply≤30W)
Ethernet Port	Ethernet Port	LAN port:10/100Mbps
	Transmission Distance	LAN port: 0-100m
PoE	PoE Protocol	IEEE802.3af/at
	PoE Power Supply	End Span
	PoE Power Consumption	≤30W
Fiber Port	Fiber Port	SFP module, LC port
	Bandwidth	155Mbps
	Transmission Distance	Depend on SFP module performance
Network Standard	Compatible with	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX/FX
LED Status Indicator	Power	1 Green light
	Ethernet	Green light on the RJ 45 Socket
	Fiber	Link, SD, FED (3 green lights)
Protection	ESD	Contact discharge 6KV; air discharge 8KV
	Lightning Protection	Power:2KV
		Signal:1KV
		Per:IEC61000-4-5
Environmental	Working Temperature	0°C~55°C
	Storage Temperature	-40°C~85°C
	Humidity (non-condensing)	0~95%
Mechanical	Dimension (L×W×H)	103mm×82mm×25mm
	Material	Aluminum Alloy