



SRX-SP201POE POE Hattı Yüksek Akım Koruyucu

Item		Description	
Network	Rated Working voltage	5V	
	Maximum Continuous working voltage	6V	
	Nominal Discharge Current (8/20us)	3KA	
	Maximum Discharge Current (8/20us)	10KA	
	Limiting Voltage Between Lines (10/700us)	Core	≤25V
		Core	≤500V
	Insulation Resistance	≥0.4MΩ	
	Insertion Loss	≤0.9dB	
	Bandwidth	(0.3-100) M	
	Transmission Rate	100Mbps	
	Reacting Time	≤1ns	
	Protective Lines	1/2.3/6	
Power	Rated Working Voltage	48V	
	Maximum Continuous Working Voltage	60V	
	Load Current	250mA	
	Nominal Discharge Current (8/20us)	5KA	
	Maximum Discharge Current (8/20us)	10KA	
	Limiting Voltage (8/20us)	250V	
	Reacting Time	≤1ns	
Environmental	Working Temperature	0°C~55°C	
	Storage Temperature	-20°C~70°C	
	Humidity (non-condensing)	0~95%	
Mechanical	Net weight	157g	
	Dimension	105mm×52mm×28mm (include interface length)	
	Material	Aluminum	
Stability	MTBF	>30000h	