

SRX-S8PP 8 Port POE Switch



Item		Description
Model		8 Ports PoE Ethernet Switch
Power	Power Supply	Power Adaptor Input
	Voltage Range	DC48V–57V
	Consumption	The Equipment<5W,PoE output<120W
Ethernet	Speed	1–8 Ethernet Port: 10/100Mbps Uplink Port: 10/100Mbps
	Transmission Distance	Down Link Port:0–100m Uplink Port:0–100m
Network Switch	Ethernet Standard	Support IEEE802.3/802.3u/802.3x/802.1p/802.1q/IEEE802.3af/at
	Backplane Bandwidth	1.8G
	Packet Forwarding Rate	1.34Mbps
	Packet Buffer	768k
	MAC	2k
Status Indicator	Power Light	1 pc(red)
	Ethernet Port Light	RJ45port 2 pcs yellow Indicates PoE, green Indicates Act/link
	Surveillance Module Light	1 pc(green)
Protection Level	Pluse Group	Level 2 Standard:IEC61000–4–4
	ESD	1a Contact Discharge Level 2 1b Air Discharge Level 2 Standard : IEC61000–4–2
	Anti–thunder Level	Level 2 Standard : IEC61000–4–5
Working Environment	Working Temperature	0℃ ~ 55℃
	Storage Temperature	–40℃ ~ 85℃
	Humidity(Non–condensing)	0 ~ 95%
Mechanical	Dimension(L*W*H) Include Port	200mm*105mm*27mm
	Out Shell	Galvanized Sheet
	Color	Black
	Weight	500g
Stability	MTBF	≥50000h