



SRX-GEC1 Gigabit Medya Dönüştürücü

	Item	Description
Power	Power Supply	Power Adapter
	Voltage Range	DC12V-24V
	Consumption	<3W
Ethernet Port	Ethernet Port	LAN Port: 10/100/1000Mbps
	Transmission Distance	LAN port: 0-150m
Fiber Port	Fiber Port	LC Port, SFP Optical Module, Single Fiber or Dual Fiber Optional
	Bandwidth	1.25Gbps
	Transmission Distance	20km, 40km, 60km, 80km, 120km Depend on SFP module performance
Network Standard	Compatible with	IEEE802.3, IEEE802.3u, IEEE802.3ab/z, 10/100/1000BASE-TX and 1000BASE-FX; IEEE802.3 X
LED Status Indicator	Power	1 Red
	Ethernet	1 Green on RJ45 Socket
	Fiber	3 Green (Link, SD, FED)
Protection	ESD	Contact Discharge 6KV
		Air Discharge 8KV
	Lightning Protection	Power:2KV
		Signal:1KV
Environmental	Working Temperature	0°C~55°C
	Storage Temperature	-40°C~85°C
	Humidity (non-condensing)	0~95%
	Per: IEC61000-4-5	
Mechanical	Dimension (L×W×H)	26mm×71mm×94mm
	Material	Aluminum Alloy
	Color	Black
	Weight	160g