



SRX-MS24PP 24 Port PoE Switch Data Sheet

Power	Power Supply	Electric Power
	Power Adapter Voltage	AC100V-240V
	Consumption	430W, Max PoE output is 380W
Network Connector	Network Port	1-24 Port: 10/100MbpsPOE network port UPLINK Port: 10/100/1000Mbps network port SFP: SFP optical fiber module port, 1000Mbps
	Transmission Distance	1-24 port:150m UPLINK port: 100m
	PoE Protocol	IEEE802.3 af, IEEE802.3 at
	PoE Power Supply	End-span
	PoE Power Consumption	every port<30W, unit<380W
Network Switch	Network Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX\LX
	Package Data Cache	9.6Mpps
	Switch Capacity	12.8G
Network Management	VLAN Standard	Based on Port VLAN
LED Status Indicator	Front Panel Indicator	1 power status indicator (red), 24 network status indicator (green), POE status indicator (red); 2 uplink Ethernet status
Protection	ESD	1a contact discharge 3 level 1b air discharge 3 level Per:IEC61000-4-2
	Communication port Lightning protection	3 level, Per: IEC61000-4-5
Environmental	Working Temperature	0°C-55°C
	Storage Temperature	-40°C-85°C
	Humidity (non-condensing)	0-95%
Mechanical	Dimension (L×W×H)	442mm×217mm×44mm
	Material	Aluminum
	Color	Black
	Weight	3.1kg
Stability	MTBF	>30000h